

# Outdoor IP Mini Fisheye Dome Camera / 4.2MP / 1.6mm Ultra-wide Angle Lens / PoE



IP Mega

4.2 MP

IP66 Outdoor

4.2 MegaPixel Resolution • 1.6mm Ultra-wide Angle Lens • Power over Ethernet (PoE) • ONVIF Compliant • H.264 • DC 12V

## FEATURES

- 2464 × 1520 resolution
- Compact design
- Support on-board storage

## SPECIFICATIONS

Camera	
Image sensor	1/3" Progressive Scan CMOS
Min. illumination	Color: 0.01lux @(F1.2, AGC ON) B/W: 0.001lux @(F1.2, AGC ON) 0 lux with IR
Shutter Speed	1/25s to 1/100,000s
Lens	1.6mm, F1.6 Angle of view: 186°(horizontal), 106°(vertical)
Lens mount	M12
Day & night	Electronic
Compression Standard	
Video compression	H.264 / MJPEG
H.264 Type	Baseline Profile / Main Profile
Video Bit Rate	32 Kbps – 8 Mbps
Image	
Max. Image Resolution	2560 x 1440
Frame rate	50Hz: 12.5fps (2560 x 1440), 25fps(1920x1080, 1280x720) 60Hz: 15fps (2560 x 1440), 30fps(1920x1080, 1280x720)
Digital Noise Reduction	3D DNR
Image Setting	Saturation, Brightness, Contrast, Hue, Sharpness, AGC, White Balance
Day/Night Switch	Auto/ Scheduled/ Alarm Trigger
Network	

Network storage	NAS
Alarm Trigger	Line Crossing, Intrusion detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP
Security	PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
Standard	User Authentication, Watermark, IP address filtering, Anonymous access
<b>Interface</b>	
Communication Interface	1 RJ45 10M/100M Ethernet interface 1 RS485 interface(-S)
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 64 GB
<b>General</b>	
Operating conditions	10 °C – 40 °C (14 °F – 104 °F) Humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	Max. 5.55W
Mount Type	Ceiling mounting, Wall mounting, Table mounting
Software Dewarping	By web component or client
Dimensions	ø119.9 x 41.2
Weight	600g